



## Conversa™ with ClearCall Power Mini-BTE

Realtime Feedback Canceller  
Intelligent Noise Reduction, ClearPath™ Processing Strategy


### HEARING AID FEATURES

- 16 channels provide high resolution signal processing
- Realtime feedback canceller reacts within milliseconds using independent narrow band detectors to provide precise and adaptive cancellation
- ClearPath™ Technology
  - Noise reduction based on intelligent signal detection system with speech weighting factors. Fast time constants provide rapid reaction to incoming signals. Choice of settings: off, moderate, maximum
  - ClearPath processing strategy applies the appropriate scheme based on input level independently across all channels to provide maximum flexibility in frequency shaping for soft, moderate and loud inputs (quiet mode expansion, linear, wide dynamic range compression, compression limiting)
- Up to three programs allowing customization for different listening environments
- Telecoil (T) mode or Microphone/Telecoil (MT) mode can be set as one of the three independent programs
- Users choose program through function switch; audible beep confirms selection
- Start up mute
- Low battery warning
- Conversa Power can be programmed using NOAH-compatible Unifit™ and Standalone Unifit
- O-M-P function switch: three positions Off–Microphone–Program
- Direct Audio Input - MLx compatible
- Manual volume control can be disabled through software
- Battery size: 13

### OPTIONS

- Tamper-resistant volume control
- Tamper-resistant battery door
- Filtered earhook
- Multi-memory Selector (MMS)
- Child-sized earhook
- Choice of shell colors

### SUITABLE FOR FITTING MODERATE TO PROFOUND HEARING LOSSES



#### Fitting Guide

Can fit audiogram configurations ranging from reverse to precipitously sloping.

### IEC 118-0 TECHNICAL DATA

Frequency Range	100-6500 Hz
Peak Gain	78 dB
Peak Output	142 dB
Reference Test Gain	58 dB
Full on Average Gain*	67 dB
Average Output*	132 dB
Reference Test Frequency	1.6 kHz
Full on Gain at 1.6 kHz	71 dB
Output at 1.6 kHz	135 dB
Typical Battery Life (Zinc Air Premium)	265 h
Current Drain at RTG	1.1 mA
Output with Inductive Input at 1.6 kHz Quiet Mode Expansion "Off"	103 dB
Equivalent Input Noise at RTG	< 15 dB
Fast Time Constant	
Attack Time	< 40 ms
Release Time	100 ms
Slow Time Constant	
Attack Time	250 ms
Release Time	300 ms
Compression Ratio	
Wide Dynamic Range Compression	4:1 to 1:1
Output Limiting	20:1


\*Average of 500, 1000, and 2,000 Hz

### IEC 118-7 2cc COUPLER TECHNICAL DATA


Frequency Range	100-6500 Hz
Peak Gain	70 dB
Peak Output	135 dB
Reference Test Gain	48 dB
Full on Gain at 1.6 kHz	61 dB
Output at 1.6 kHz	125 dB

Note: Technical data generated with Quiet Mode Expansion "On"


# CONVERSA POWER DIGITAL MINI-BTE IEC 118-0 EAR SIMULATOR SPECIFICATIONS




Input sound pressure level: 90 dB  
Volume Control: full on




Input sound pressure level: 50 dB  
Volume Control: full on



Input at 1600 Hz  
Volume Control: as shown




Input sound pressure level: 60 dB  
Volume Control: RTG




Input: 1 mA/m  
Volume Control: full on

## IEC 118-7 2cc COUPLER



Input sound pressure level: 90 dB  
Volume Control: full on



Input sound pressure level: 60 dB  
Volume Control: RTG

### TEST CONDITIONS

RTG-IEC: Reference Test Gain of the Volume Control: 3.2  
BATTERY: 13 Zinc Air Premium  
SOURCE: Voltage 1.3 V  
Impedance 6 Ohms  
EARHOOK: Unfiltered  
TUBING: Length 25 mm,  
Inside Diameter 1.93 mm  
Refer to: "Summary of Test  
Conditions and Limits"  
for more details.

**AID MARKING:** Conversa P  
**with MMS:** Conversa P\_

### COMPLIANCE

Our products are designed to meet all of the limits required when tested in accordance with the applicable standard.

### REFERENCES

IEC: International Electrotechnical Commission Publication 118-0, 118-7 (1983)

European Standard EN60118/A1 February, 1994

We reserve the right to change specification data without notice as improvements are introduced.

This product is manufactured under the protection of U.S. Patent #4349082 & #5204917.

Caution: Hearing aids and batteries can be harmful if swallowed or improperly used.

Sound pressure level of this hearing aid exceeds 132 dB SPL.



### CORPORATE OFFICE

Kitchener, Ontario, Canada  
877 492 6244; 519 895 0100  
fax 519 895 0108

### CANADA

Cambridge, Ontario  
800 265 8255; 519 650 9111  
fax 800 949 6663

### U.S.A.

Plymouth, Minnesota  
800 888 8882; 763 744 3300  
fax 763 557 8828

### INTERNATIONAL

Kitchener, Ontario, Canada  
519 895 0100  
fax 519 895 2318

### EUROPE

Bremen, Germany  
49 421 43 87 90  
fax 49 421 48 81 56

www.unitronhearing.com